

Limited Series Page 4

Summit 65

The Summit 65 is our new extension of our popular Pinnacle 55 linear. With an extra 10" to play with the Summit 65 takes what everyone loves about the Pinnacle one step further. Doing so with and extraordinary flame that only bumps up the BTU's to a manageable 38,000 BTU's. Meaning you can turn the fireplace on and leave it on, amazing for a linear this size!

Plus, only 17-1/2" deep for framing. Again, amazing!

Summit
High 38,000BTU's
Low 27,000BTU's
Framing Dim:
39"H X 68-1/4"W X 17-1/2"D
Internal Ceiling = 58"Min
Mantle Height = 45"Min
* Safety Screen attached to unit.

Options and Accessories See Bottom of Page

-Deluxe System Only

-Porcelain Panels Included



Noble 36

This 36" For those that are looking for a little more punch from their fireplace without taking up huge amounts of space, the Noble 36 is pound for pound the best bet out there. It boasts 26,000 BTU's and is proof good things come in small packages as it's framing is only 36" wide and 15" deep. A very compact little unit for all that heat!

Media: NB 4 Piece Log Set

Noble
High 26,000BTU's
Low 18,000BTU's
Framing Dim:
37"H X 38"W X 15"D
Internal Ceiling = 52" Min
Mantle Height = 42" Min
* Safety Screen attached to unit.

Options and Accessories See Bottom of Page

in Went skind or had

-Deluxe System Only

-Porcelain Panels Included

Accessories

Remote

Deluxe System *Standard for all Limited units/Option for all Elite units

- Electronic Ignition


- Fan Kit w/ 6 stage adjustable fan control

- Modulating flame control

- Deluxe remote w/ 7 day programmable thermostat

Basic Black Surround









Dimensional Chart and Features



Model	BTU	S	Vent	He	ight	Wi	dth	De	oth	Viewir	ng Area	Efficiency	
	Natural Gas	Propane		Actual	Framing	Actual	Framing	Actual	Framing	Height	Width	EnerGuide	
- AF	Hi 30,000	27,000	Top	00.000	20.00	201 44	11 4/12	10.4445	44.400	40 4/07	40 4/00	407	CO 500/
Essence 45	Lo 22,000	19,500	4" & 7"	29.86°	39°	44-1/4"	48-1/4"	14-1/2"	16-1/2"	16-1/2"	42"	69.50%	
Standard Foatures:			Surrounde: (Mandatony)							Ontions:			

Basic Black Surround w/Safety Screen

Decorative Black Surround w/Safety Screen

Decorative Stainless Surround w/Safety Screen

Linear Design
 30,000BTU
 Full Deluxe System
 Porcelain Liner
 Ceramic Glass
 Dual Stainless Steel Pan Burner
 Black Glass and Grey Pebble Kit

Driftwood & Media Kit



Model	BTU	's	Vent	He	ight	Wi	dth	De	pth	Viewir	ng Area	Efficiency
	Natural Gas	Propane		Actual	Framing	Actual	Framing	Actual	Framing	Height	Width	EnerGuide
Dippoolo FF	Hi 36,000	32,000	Top	29.86"	39"	54.29"	58-1/2"	14-1/2	17-1/2"	10 1/2"	E2 2/4"	68.75%
Pinnacle 55	Lo 21,250	26,000	4" & 7"	29.00	39	54.29	30-1/2	14-1/2	17-1/2	10-1/2	52-3/4	00.75%

see page 3

- Linear Design
- 36,000BTU
- Full Deluxe System
- Porcelain Liner
- Ceramic Glass
- Dual Stainless Steel Pan Burner
- Black Glass & Grey Pebble Kit

Basic Black w/Safety Screen
 Decorative Black w/Safety Screen
 Decorative Stainless w/Safety



Model	BTU	's	Vent	He	ight	Wi	dth	De	pth	Viewir	ng Area	Efficiency
	Natural Gas	Propane		Actual	Framing	Actual	Framing	Actual	Framing	Height	Width	EnerGuide
Summit 65	Hi 38,000	38,000	Top	29.86"	39"	64 1/4"	68-1/4"	14-1/2"	17 1/2"	10 1/2"	62 2/4"	69.10%
Summit 65	Lo 27,000	26,000	4" & 7"	29.00	39	04-1/4	00-1/4	14-1/2	17-1/2	10-1/2	02-3/4	09.10%

see page 4

- Linear Design
- 38,000BTU
- Full Deluxe System
- Porcelain Liner
- Borosilicate Glass
- Dual Stainless Steel Pan Burner
- Black Glass & Grey Pebble Kit

ato	ry)	Options:
	Clean Face Black w/Safety Screen	Driftwood
	Basic Black w/Safety Screen	Media Kits



Model	BTU's Vent		Height		Width		Depth		Viewing Area		Efficiency	
	Natural Gas	Propane		Actual	Framing	Actual	Framing	Actual	Framing	Height	Width	EnerGuide
Noble 26	Hi 26,000	26,000	Top	28-1/2"	37"	39-1/2"	38"	13"	15"	16-1/2"	29"	TBD
Noble 36	Lo 18,000	18,000	4" & 7"	20-1/2	31	39-1/2	30	13	15	10-1/2	29	IBD

Standard Featur	es:	Surrounds:					
see page 4	Clean Face Design	Included on unit					
	• 30,000BTU						
	 Full Deluxe System 						
	Porcelain Liner						
	Ceramic Glass						
	 4 pc Traditional Log Set 						

Specifications:

Unit Certified under joint Canadian and American standard ANSI Z21.88-2009 or the current CSA 2.33-2009